

## SYNTH SX 5W30

SYNTH SX 5W30 is a high performance engine oil of the latest generation, specially designed to meet the strict requirements of manufacturers and composed of non-conventional base oils and high quality additives.

SYNTH SX 5W30 meets the following performance criteria:

- API SN/CF
- ACEA A3/B3/B4
- VW 502.00/505.00
- MB 229.3
- Porsche/BMW Longlife-01
- Opel GM-LL-B-25

### ADVANTAGES :

A universal, fuel economy, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

### TYPICAL CHARACTERISTICS :

Test	Method	Unit	Average result
Density @15°C	ASTM D4052	g/ml	0,858
Viscosity @-30°C	ASTM D5293	mPa.s	6280
Viscosity @40°C	ASTM D445	mm <sup>2</sup> /s	66
Viscosity @100°C	ASTM D445	mm <sup>2</sup> /s	11,1
Viscosity Index	ASTM D2270		162
Flash point COC	ASTM D92	°C	214
Pour point	ASTM D6892	°C	-42
Total Base Nummer	ASTM D2896	mgKOH/g	10,0
Sulphated Ash	ASTM D874	Mass %	1,0

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

